

SealRex - OR O-ring & Seal-ring

- High quality rubber O-ringen en sealringen
- Substantial material range possible like NBR, Viton, EPDM, Silicone etc.
- Standard colour black—other colours possible on request
- Over 3.300 different standard and non-standers sizes
- Shore hardness (duro) possible from 30 to 90 shore A
- Standard sizes in any known (U.S. / JAPAN etc.) Norms (AS, BS, R, P, G etc.)



Norm Type	Standard	From ØID x heighth mm	To ØID x heighth mm	PDF-list all sizes	Minimal quantity
Design by international standard norm					
AS568	USA	Ø0.74 x 1.02	Ø658.88 x 6.99	AS568-USA	1.000
BS1516	UK	Ø2.90 x 1.78	Ø413.60 x 6.99	BS1516-UK	1.000
R	France	Ø2.40 x 1.90	Ø393.07 x 6.99	R-FRANCE	1.000
P	Japan	Ø2.80 x 1.90	Ø399.5 x 8.40	PG-JAPAN	1.000
G	Japan	Ø24.40 x 3.10	Ø299.3 x 5.70	PG-JAPAN	1.000
Non-standard sizes always possible. Just send innersize and thickness with material-type for an offer					
Shore hardness up to 90 shore					
O-rings possible in these materials:					
NBR-HNBR-XNBR-EPDM-VMQ-CR-FKM-AFLAS-FVMQ-FFKM-PTFE-PU-NR-SBR-IIR-ACR					
Most used colours for O-rings (Pantone):					
187C-1665C-7404C-3298C-280C-431C-187C-4975C-1C					

